



AIO

DC | Fast Charging
180 kW All-In-One



CHARGING
YOUR
FUTURE

NOCH POWER Inc.

26632 Towne Centre Dr # 300,
Foothill Ranch, CA 92610
hello@nochpower.com

CCS-1 - DC Charging	L3A - 120	L3A - 150	L3A - 180
Max Power Rating	120kW	150kW	180kW
Output Voltage Range	200 – 920 VDC		
Output Current	200A max.	500A max	500A max.
Cable Length	15.4 ft.		

CHAdeMO - DC Charging	
Max Power Rating	100kW
Output Voltage Range	200 – 500 VDC
Output Current	200A max.
Cable Length	13 ft.

General System Specifications	
Efficiency	> 94%
Power Factor	> 0.99 full load
Humidity	95% non-condensing
Operating Temperature	-22°F to 122°F, (-30°C to 50°C)
Altitude	Up to 6,000 ft
Protection Rating	NEMA 3R
Dimensions (WxDxH)	32.3"W x 30.3"D x 86.1"H (Footprint)
Weight	~1544 lbs

AC Input - Grid Connection			
AC Connection	AC 3-phase L1, L2, L3, PE		
Input Voltage	480 VAC, 3 Phase, +10% / -15%		
Frequency	47 – 63 Hz		
Input Current Rating	158A	190A	238A

Connectivity	
Communication	LAN · WiFi · Cellular
Protocol	OCPP 1.6J (2.0.1 Coming Soon)

Key Features	
CCS-1 CHAdeMO NACS	Liquid Cooled Cables
Simultaneous Charging	15" or 32" Touchscreen
Credit Card and RFID	Modular System
Integrated Cord Retraction	ISO 15118 Certified

